

Name: S-PRW15158254B(440gsm) Blockout two side

Description:

**Technical Date Sheet**

<b>Item</b>	<b>Value</b>	<b>Unit</b>	<b>Test Method</b>
Base Fabric:	High Tenacity Yarns 100%PES	Denier/DTEX	<b>DIN EN ISO2060</b>
Threads& Yarn	150*150/165*165 82*54/32*21, woven	Denier/DTEX fd/in	<b>DIN60001</b>
Total Weight:	440/12	gsm/oz	<b>DIN53352 BS3424 method5A</b>
Weight of Fabric:	94	gsm	<b>DIN53352 BS3424method5B</b>
Weight of Pvc Coating:	346	gsm	<b>DIN53352 BS3424 method5B</b>
Breaking Strength		N/5CM	<b>DIN53354 BS3424method6A</b>
Tearing Strength:		N/5CM	<b>DIN53356 BS3424method7A</b>
Adhesion:		N/5CM	<b>DIN53357 BS3425 method9B</b>
Max Seamless Width:	2.5	Meter	
Suitable temperature:	-20~ +70	°C	<b>DIN53357 BS3425 method10</b>
UV Protection:	Optional		
Lacquering:	3555(Acrylic), 3483(Acrylic),7584(PVDF)		
Fire Retardant:	M2 ( France), DIN75200-B1 (Germany), NFPA701 (U.S.A.)		
Environmental	EN-71, RoHs, REACH		