

Name: S-TFW552828(450gsm) Frontlit

Description:

Technical Date Sheet

| Item | Value | Unit | Test Method |
|------------------------|---|----------------------|---------------------------------|
| Base Fabric: | High Tenacity Yarns 100%PES | Denier/DTEX | DIN EN ISO2060 |
| Threads& Yarn | 500*500/605*605 28*28/11*11, woven | Denier/DTEX fd/in | DIN60001 |
| Total Weight: | 450/13 | gsm/oz | DIN53352 BS3424 method5A |
| Weight of Fabric: | 129 | gsm | DIN53352 BS3424method5B |
| Weight of Pvc Coating: | 321 | gsm | DIN53352 BS3424 method5B |
| Breaking Strength | | N/5CM | DIN53354 BS3424method6A |
| Tearing Strength: | | N/5CM | DIN53356 BS3424method7A |
| Adhesion: | | N/5CM | DIN53357 BS3425 method9B |
| Max Seamless Width: | 3.2 | Meter | |
| Suitable temperature: | -20~ +70 | °C | DIN53357 BS3425 method10 |
| UV Protection: | Optional | | |
| Lacquering: | 3555(Acrylic), 3483(Acrylic),7584(PVDF) | | |
| Fire Retardant: | M2 (France), DIN75200-B1 (Germany), NFPA701 (U.S.A.) | | |
| Environmental | EN-71, RoHs, REACH | | |